

CAVO TELEFONICO TRR / TRR PHONE CABLE



TWISTED PAIRS



IMPIEGO APPROPRIATO / APPROPRIATE USE

Utilizzato nel collegamento di impianti telefonici interni. Non ammessa la posa interrata, neanche protetta.
Suitable for phone installations on inside. Not suitable for buried laying, even if protected.

	CARATTERISTICHE/ CHARACTERISTICS	DESCRIZIONE/ DESCRIPTION	NORME/ REFERENCE
	Tipo di cavo Type of cable	TRR	
	Tensione nominale Nominal Voltage	U ₀ /U 300/300V	
1	Conduttore Core	Conduttore di rame stagnato rigido diam. 0,60 mm Rigid tinned copper diam. 0,60 mm	EN 60228
2	Binatura a coppie Pair-in-pairs	PVC tipo T12 T12 PVC type	
3	Guaina Sheath	PVC tipo TM2, colore grigio RAL 7001 TM2 PVC type, grey colour RAL 7001	EN 50363
	Campo di temperatura Temperature range	-5°C / +70°C	
	Temperatura massima di corto circuito Maximum short circuit temperature	150°C	
	Tensione di prova Testing voltage	1500 V CC	
	Imballo Package	Matasse mt.250 fino al 16 coppie telefonico. 1 coppia + T disponibile da mt.100 - Bobine 250 m rings up to 16 pair-in-pairs. 1 pair + T available from 100 m. - Drums	

NORME RIF. GENERALI / GENERAL REFERENCE

CEI 46-5

IDENTIFICAZIONE CONDUTTORI / CORE IDENTIFICATION

CEI UNEL 00724

MULTISTANDARD
CABLES

CONTROL
CABLES

DATA
CABLES

ENERGY
CABLES

SPECIAL
CABLES

SHIELDED
CABLES

ARMOURED
CABLES

UTILITIES

CAVO TELEFONICO TRR / TRR PHONE CABLE

Formazione <i>Construction</i>	Diametro esterno indicativo <i>Approximate external diameter</i>	Peso indicativo cavo <i>Approximate cable weight</i>	Resistenza elettrica max a 20° C <i>Max electric resistance at 20°C</i>
n x mm ²	mm	kg/km	Ohm/km
1 x 2 x 0.60	3.4	12	67.90
1 x 2 x 0.60 + T	3.6	15	67.90
2 x 2 x 0.60	4.9	31	67.90
2 x 2 x 0.60 + T	5.0	36	67.90
3 x 2 x 0.60	5.2	39	67.90
4 x 2 x 0.60	5.7	56	67.90
5 x 2 x 0.60	6.2	68	67.90
6 x 2 x 0.60	6.8	89	67.90
8 x 2 x 0.60	7.4	110	67.90
11 x 2 x 0.60	8.9	123	67.90
16 x 2 x 0.60	9.8	176	67.90
21 x 2 x 0.60	11.4	210	67.90

MULTISTANDARD
CABLES

CONTROL
CABLES

DATA
CABLES

ENERGY
CABLES

SPECIAL
CABLES

SHIELDED
CABLES

ARMOURED
CABLES

UTILITIES