

**IMPIEGO APPROPRIATO / APPROPRIATE USE**

Cavi idonei per alimentazione di lampade da tavolo o apparecchi portatili leggeri. Non adatto per impianti elettrici.
Suitable for conveying electrical signal of desk lamp or light electric equipments. Not suitable for electric installations.

| | CARATTERISTICHE/ CHARACTERISTICS | DESCRIZIONE/ DESCRIPTION | NORME/ REFERENCE |
|---|--|---|---------------------|
| | Tipo di cavo Type of cable | Piattina costa stretta | |
| | Tensione nominale Nominal Voltage | U ₀ /U 300/300V | |
| 1 | Conduttore Core | Rame rosso/rame stagnato Red copper/tinned copper | EN 60228 |
| 2 | Isolamento Insulation | PVC tipo TM2 TM2 PVC type | EN 50363 |
| | Campo di temperatura Temperature range | -10°C / +70°C | |
| | Temperatura massima di corto circuito Maximum short circuit temperature | 150°C | |
| | Tensione di prova Testing voltage | 2000 V AC | |
| | Imballo Package | Matasse mt.100 in termoretraibile - Bobine 100 m thermo-shrinking material coils - Drums | |

NORME RIF. GENERALI / GENERAL REFERENCE

EN 60228; EN 50363

IDENTIFICAZIONE CONDUTTORI / CORE IDENTIFICATION

Argento, bianco, nero, oro, marrone, rosso/nero.
Silver, white, black, gold, brown, red/black.

| Formazione Construction | Diametro esterno indicativo Approximate external diameter | Peso indicativo cavo Approximate cable weight |
|----------------------------|---|--|
| mm ² | mm | kg/km |
| 2 x 0.50 | 2 x 2.10 | 16 |
| 2 x 0.75 | 2 x 2.30 | 21 |
| 2 x 1 | 2 x 2.50 | 27 |
| 2 x 1.5 | 2 x 2.90 | 37 |
| 2 x 2.5 | 2 x 3.50 | 58 |

MULTISTANDARD
CABLES

CONTROL
CABLES

DATA
CABLES

ENERGY
CABLES

SPECIAL
CABLES

SHIELDED
CABLES

ARMOURED
CABLES

UTILITIES